

**RESTORE QUICKSKIM****1. DESCRIPTION**

- **Restore Quickskim** is recommended to give a perfectly smooth weatherproof finish to rough or uneven plaster.
- **Restore Quickskim** is ready mixed for easy off use, it will skim up to 2mm thick and is specially formulated to adhere strongly to plaster.
- Simply skim it on and smooth it off, it will set hard in 4 hours to a white, weatherproof and alkali resistant finish that does not need to be primed before painting.
- Use outdoors & indoors for plaster, plasterboard and painted masonry surfaces.

**2. TECHNICAL DATA**

Product Code Colour Shelf life Packaging Flashpoint	RES 1053 White 6 Months 1L, 5L, 20L
Viscosity S.G (Weight) Solids per volume Solids per mass	Paste 1.82 kg/l 67-71% 82-85%
Cleaning Thinning	Water

**3. FEATURES**

- **Restore Quickskim** should be leveled and smoothed prior to drying, because once dry, it is very laborious to sand it smooth.
- Excellent flexibility, hardness and weather resistance
- Extremely versatile – can be used to repair a variety of surfaces.
- Simple to use – no special mixing required.
- Ready – mixed filler based on a powerful adhesive resin.

**4. LIMITATIONS**

- The repair should be protected from ingress of water during the drying period.
- Although it may be left unpainted it should not be exposed to permanently wet conditions. It is therefore advisable to overcoat **Restore Quickskim** with either emulsion paint or enamel paint systems.
- **Restore Quickskim** is difficult to sand and is best smoothed while wet. Should sanding still be necessary, wet sand with 100 grit waterproof paper for the best results.

**5. SURFACE PREPARATION**

- Remove dust, grease and grime from surface.
- Remove enamel paint in poor conditions with Restore Deep Penetrating Paint Stripper
- Prime filled cracks with **Impa Plaster Primer** before overcoating.
- Paint nail heads inside cracks with Impa Zinc Phosphate Primer.

**6. APPLICATION**

- **Restore Quickskim** should be leveled and smoothed prior to drying, because once dry, it is very laborious to sand it smooth.
- Excellent flexibility, hardness and weather resistance
- Excellent versatile – can be used to repair a variety surface.
- Simple to use – no special mixing required
- Ready – mixed filler based on a powerful adhesive resin.



## 7. PRECAUTIONS

- Application should be avoided in cold and moist weather conditions.
- **Do Not** apply the product at surface temperatures below 6°C (minimum of 2°C above dew point) and temperatures above 40°C
- **Do Not** apply if ambient temperature is less than 10°C or more than 40°C.
- **Do Not** apply if relative humidity temperature is less than 10°C or more than 85. °C
- Always keep paint out of reach of children.
- Avoid inhalation of powder/dust
- Ensure good ventilation during application and drying
- In case of skin contact, wash with soap and water or a recognized skin cleaner
- Harmful if swallowed. Do not induce vomiting. Seek medical attention.
- Avoid contact with eyes. In case of eye contact, wash with copious amounts of water and consult a doctor.
- Refer to Material Safety Data Sheet for complete information.

### Environmental Health & Safety Information

**DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE.**

**HARMFUL IF SWALLOWED. CONTAINS POTASSIUM HYDROXIDE. AVOID CONTACT WITH SKIN.**

May cause permanent skin damage and severe respiratory system irritation. Use with adequate ventilation. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, **DO NOT** induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN AND ANIMALS – DO NOT TAKE INTERNALLY.**

**Refer to Material Safety Data Sheet for additional health and safety information.**

**IN CASE OF FIRE:** Use foam, CO<sub>2</sub>, dry chemical, or water fog.

**SPILL** – Absorb with inert material and dispose of as specified under **Thinning/Clean-up.**

### **DISCLAIMER**

*The technical information contained in this document are given in good faith and are meant to be used as a guideline by the specifier or user. Whilst we are confident about the quality of our products, we cannot accept any liability for the incorrect use or application of our products. Surface preparation forms an integral part of the scope of works and it is expected that the highest standards are maintained during surface preparation and application, to ensure that our products perform as intended. Always ensure to use the same product batch numbers, refrain from doing spot touch-ups and paint surfaces from corner to corner to prevent colour and sheen variance.*

*Please note that all our latest Product Data Sheets and Material Safety Data Sheets are available for viewing on our website at [www.prepfit.co.za](http://www.prepfit.co.za). All information listed is owned or used under licence of Prepfit and its related companies. © Prepfit (Pty) Ltd. All rights reserved.*